



# THE NXS™ FAMILY OF RIFLESCOPES: HOW LEGENDS ARE MADE.

For over 20 years, Nightforce NXS™ riflescopes have performed impeccably in the most brutal, unforgiving environments on earth. Conceived to exceed U.S. military performance standards, they have served reliably in theaters of war around the globe.

Serious hunters rely upon them for their ability to endure repeated recoil, blistering heat, sub-zero cold, rain, sleet, snow, mountains, rocks, falls, horses and even airline baggage handlers.

NXS™ riflescopes are built to standards that exceed virtually any other riflescope on the market. Each must pass a battery of tests—including side and front impact—that would destroy an ordinary

optic. Only the highest quality, most durable components are used in NXS™ riflescopes, assuring a lifetime of repeatable precision. NXS™ lenses are painstakingly bedded with our proprietary Mil-Spec formulation, reducing any glass-to-metal contact that can result in breakages, stress, misalignment, and thermal shock. It's how legends are built.

## 2.5-10x42

Magnification range	2.5-10x
Focal plane	Second
Body tube diameter	30 mm
Overall length	11.9 in/302 mm
Mounting length	5.1 in/130 mm
Weight	20.5 oz/581 g
Click value	.250 MOA or .1 MRAD
Internal adjustment range	E: 100 MOA/29 MRAD W: 100 MOA/29 MRAD
Parallax adjustment	25 yd-∞
Eye relief	3.3 in/85 mm
Field of view @ 100 yd/m	2.5x: 44.0 ft/14.7 m 10x: 11.0 ft/3.7m
Exit pupil	2.5x: 15.5 mm 10x: 4.4 mm
Illumination	Digillum™
Elevation feature	ZeroStop®
Power Throw Lever	Standard
Reticles available	MOAR™ MIL-R™



## 3.5-15x50

Magnification range	3.5-15x
Focal plane	Second
Body tube diameter	30 mm
Overall length	14.7 in/373 mm
Mounting length	6.1 in/155 mm
Weight	30.0 oz/850 g
Click value	.250 MOA
Internal adjustment range	E: 110 MOA W: 80 MOA
Parallax adjustment	50 yd-∞
Eye relief	3.9 in/99 mm
Field of view @ 100 yd/m	3.5x: 27.6 ft/9.2 m 15x: 7.3 ft/2.4 m
Exit pupil	3.5x: 14.3 mm 15x: 3.6 mm
Illumination	Analog
Elevation feature	ZeroStop®
Power Throw Lever	Accessory
Reticles available	MOAR™



## 5.5-22x50/56

	5.5-22x50	5.5-22x56
Magnification range	5.5-22x	5.5-22x
Focal plane	Second	Second
Body tube diameter	30 mm	30 mm
Overall length	15.1 in/384 mm	15.2 in/385 mm
Mounting length	6.6 in/168 mm	6.6 in/168 mm
Weight	31.0 oz/879 g	32.0 oz/907 g
Click value	.250 MOA	.250 MOA
Internal adjustment range	E: 100 MOA W: 60 MOA	E: 100 MOA W: 60 MOA
Parallax adjustment	50 y-∞	50 y-∞
Eye relief	3.7 in/95 mm	3.9 in/99 mm
Field of view @ 100 yd/m	5.5x: 17.5 ft/5.8 m 22x: 4.7 ft/1.6 m	5.5x: 17.5 ft/5.8 m 22x: 4.7 ft/1.6 m
Exit pupil	5.5x: 9.1 mm 22x: 2.3 mm	5.5x: 10.2 mm 22x: 2.5 mm
Illumination	Analog	Analog
Elevation feature	ZeroStop®	ZeroStop®
Power Throw Lever	Accessory	Accessory
Reticles available	MOAR™ MOAR-T™	MOAR™ MOAR-T™



## 8-32x56

Magnification range	8-32x
Focal plane	Second
Body tube diameter	30 mm
Overall length	15.9 in/404 mm
Mounting length	6.7 in/170 mm
Weight	34.0 oz/964 g
Click value	.250 MOA
Internal adjustment range	E: 65 MOA W: 45 MOA
Parallax adjustment	50 yd-∞
Eye relief	3.9 in/98 mm
Field of view @ 100 yd/m	8x: 12.1 ft/4.0 m 32x: 3.1 ft/1.0 m
Exit pupil	8x: 7.0 mm 32x: 1.8 mm
Illumination	Analog
Elevation feature	ZeroStop®
Power Throw Lever	Accessory
Reticles available	MOAR™ MOAR-T™



# NIGHTFORCE®

RUGGED. RELIABLE. REPEATABLE.

Go to [nightforceoptics.com](http://nightforceoptics.com) to find a dealer near you.

Nightforce is a registered trademark of Nightforce Optics. © 2020 Nightforce Optics. All rights reserved.