



THE NX8™ FAMILY OF RIFlescOPES: THE HEIR APPARENT TO A LEGEND

The NX8 family of riflescopes are an evolution of Nightforce's legendary NXS series, which have been proven by shooters, hunters, and professionals around the world. NX8 riflescopes pair the reliability of the NXS line with the latest advances in optical, mechanical, and electrical design. The use of ED lens elements allows for a short overall length while providing excellent image quality and clarity.

An 8x zoom ratio and cutting-edge reticle designs in both first and second focal plane provide the versatility needed to make shots from close to long-range. Whether you are a hunter, shooter, or professional, the NX8 family of multi-use optics put your capabilities on a whole new level.

1-8x24 F1

	Capped	ZeroStop®
Magnification range	1-8x	1-8x
Focal plane	First	First
Body tube diameter	30 mm	30 mm
Overall length	8.7 in/222 mm	8.7 in/222 mm
Mounting length	5.7 in/144 mm	5.7 in/144 mm
Weight	17.3oz/490g	17.6oz/499g
Click value	.500 MOA or .2 MRAD	.500 MOA or .2 MRAD
Internal adjustment range	E: 100 MOA/30 MRAD W: 100 MOA/30 MRAD	E: 100 MOA/30 MRAD W: 100 MOA/30 MRAD
Parallax adjustment	Fixed @ 125 m	Fixed @ 125 m
Eye relief	3.7 in/95 mm	3.7 in/95 mm
Field of view @ 100 yd/m	1x: 106.0 ft/35.3 m 8x: 13.2 ft/4.4 m	1x: 106.0 ft/35.3 m 8x: 13.2 ft/4.4 m
Exit pupil	1x: 7.9 mm 8x: 3.0 mm	1x: 7.9 mm 8x: 3.0 mm
Illumination	Daylight visible, externally adjustable	Daylight visible, externally adjustable
Elevation feature	Capped, finger-adjustable	ZeroStop®
Power Throw Lever	Standard	Standard
Reticles available	FC-DMx™ ●● FC-MOA™ ●	FC-MOA™ ●● FC-MIL™ ●



2.5-20x50 F1/F2

	2.5-20x50 F1	2.5-20x50 F2
Magnification range	2.5-20x	2.5-20x
Focal plane	First	Second
Body tube diameter	30 mm	30 mm
Overall length	12.0 in/305 mm	12.1 in/308 mm
Mounting length	5.4 in/138 mm	5.4 in/138 mm
Weight	28.3 oz/802 g	28.6 oz/811 g
Click value	.250 MOA or .1 MRAD	.250 MOA or .1 MRAD
Internal adjustment range	E: 110 MOA/32 MRAD W: 80 MOA/23 MRAD	E: 110 MOA/32 MRAD W: 80 MOA/23 MRAD
Parallax adjustment	11 yd-∞	11 yd-∞
Eye relief	3.5 in/88 mm	3.5 in/88 mm
Field of view @ 100 yd/m	2.5x: 41.8 ft/13.9 m 20x: 7.0 ft/2.3 m	2.5x: 36.7 ft/12.2 m 20x: 6.1 ft/2.0 m
Exit pupil	2.5x: 7.1 mm 20x: 2.5 mm	2.5x: 5.9 mm 20x: 2.5 mm
Illumination	Digillum™	Digillum™
Elevation feature	ZeroStop®	ZeroStop®
Power Throw Lever	Standard	Standard
Reticles available	MOAR™ ●● MIL-C™ ●● MIL-XT™ ●● MOA-XT™ ● TREMOR3™ ●●	MOAR-CF2™ ●●● MIL-CF2™ ●●



4-32x50 F1/F2

	4-32x50 F1	4-32x50 F2
Magnification range	4-32x	4-32x
Focal plane	First	Second
Body tube diameter	30 mm	30 mm
Overall length	13.4 in/340 mm	13.5 in/343 mm
Mounting length	5.7 in/145 mm	5.7 in/145 mm
Weight	28.6 oz/811 g	28.9 oz/819 g
Click value	.250 MOA or .1 MRAD	.250 MOA or .1 MRAD
Internal adjustment range	E: 90 MOA/26 MRAD W: 70 MOA/20 MRAD	E: 90 MOA/26 MRAD W: 70 MOA/20 MRAD
Parallax adjustment	11 yd-∞	11 yd-∞
Eye relief	3.5 in/88 mm	3.5 in/88 mm
Field of view @ 100 yd/m	4x: 26.1 ft/8.7 m 32x: 4.6 ft/1.5 m	4x: 26.0 ft/8.7 m 32x: 4.6 ft/1.5 m
Exit pupil	4x: 7.3 mm 32x: 1.6 mm	4x: 6.7 mm 32x: 1.6 mm
Illumination	Digillum™	Digillum™
Elevation feature	ZeroStop®	ZeroStop®
Power Throw Lever	Standard	Standard
Reticles available	MOAR™ ●● MIL-C™ ●● MIL-XT™ ●● MOA-XT™ ● TREMOR3™ ●● TREMOR5™ ●	MOAR-CF2D™ ●●● MIL-CF2D™ ●●



Go to nightforceoptics.com for more information.

Nightforce is a registered trademark of Nightforce Optics. © 2023 Nightforce Optics. All rights reserved. Rev. 0323T5JULY

NIGHTFORCE
RUGGED. RELIABLE. REPEATABLE.